



Product Catalog



**ITT Industries**  
*Engineered for life*



Pumps - Tables

Capacity GPH	Model No.	Watts	Volts	Amps @12v	Amps @13.6v	Fuse Size	Height mm	Width mm	Weight Kg	HoseDiameter mm	Panel Switches	Float Switches
<b>RULE-MATE AUTOMA TED BILGE PUMPS</b>												
500	RM500	-	12DC	1.9	2.5	2.5	101.6	127	0.37	19.0	41, 43, 45	-
500	RM500-24	-	24DC	1.0@24v	1.3@27.2v	1.5	101.6	127	0.37	19.0	42, 44, 45	-
750	RM750	-	12DC	2.8	4.0	5	101.6	127	0.37	19.0	41, 43, 45	-
750	RM750-24	-	24DC	1.4@24v	2.0@27.2v	2.5	101.6	127	0.37	19.0	42, 44, 45	-
1100	RM1100	-	12DC	3.3	5.0	6	101.6	127	0.40	28.6	41, 43, 45	-
1100	RM1100-24	-	24DC	1.4@24v	2.0@27.2v	2.5	101.6	127	0.40	28.6	42, 44, 45	-
1500	RM1500	-	12DC	4.8	7.0	9	152	185	1.6	28.6	41, 43, 45	-
1500	RM2000	-	12DC	8.4	12.0	15	152	185	1.8	28.6	41, 43, 45	-
<b>AUTOMATIC SERIES BILGE PUMPS</b>												
8000	174S	-	12DC	15.5	20.0	25	279	305	5.8	76.0	-	-
4000	56S	-	12DC	15.5	20.0	25	235	124	2.5	51.0	49	-
3700	55S	-	12DC	15.5	20.0	25	209.5	124	2.5	38	49	-
2800	A53S	175	110AC	-	-	-	222	124	2.5	38	-	-
2800	A55S-24	175	110AC	-	-	-	222	124	2.6	38	-	-
2000	53S	-	12DC	8.4	12.0	15	196.8	120.6	1.8	28.6	49	-
1800	A53S	100	110AC	-	-	-	196.8	120.6	1.8	28.6	-	-
1800	A53S-24	100	110AC	-	-	-	196.8	120.6	1.9	28.6	-	-
1100	27S	-	12DC	3.3	5.0	6.0	114	60.3	0.34	28.6	49	-
500	25S	-	12DC	1.9	2.5	2.5	102	60.3	0.31	19.0	49	-
500	25S-24	-	24DC	0.9@24v	1.3@27.2v	1.5	102	60.3	0.31	19.0	49	-
500	25S-6	-	12DC	1.9	2.5	2.5	102	60.3	0.34	19.0	49	-
500	25S-6WC	-	12DC	1.9	2.5	2.5	102	60.3	0.34	19.0	49PWC	-
<b>NON-AUTOMATIC BILGE PUMPS</b>												
8000	174D	-	12DC	15.5 (2 ea)	20.0 (2 ea)	25 (2 ea)	196.8	305	4.9	76.0	-	-
4000	56D	-	12DC	15.5	20.0	25	196.8	124	2.5	51.0	41, 43, 45, 49	37, 40
4000	56D-24	-	24DC	6.9@24v	10.0@27.2v	15	196.8	124	2.5	51.0	41, 43, 45, 49	35, 37, 40
4000	56D-32	-	32DC	5.0@32v	7.5@36.3	10	196.8	124	2.5	51.0	41, 43, 45, 49	35, 37, 40
3800*	17A	-	12DC	15.5	20.0	25	133	216	2.6	38	49	-
3700	14A	-	12DC	15.5	20.0	25	184	124	2.4	38	41, 43, 45, 49	37, 40
3700	14A-6UL	-	12DC	15.5	20.0	25	184	124	2.4	38	41, 43, 45, 49	35, 37, 40
3700	16A	-	24DC	6.9 @ 24v	10.0 @ 27.2v	15	184	124	2.4	38	42, 44, 45, 49	35, 37, 40
3700	15A	-	32DC	5.0 @ 32v	7.5 @ 36.3v	10	184	124	2.4	38	42, 44, 45, 49	35, 37, 40
3700	18A	-	24DC	6.9 @ 24v	10.0 @ 27.2v	15	133	216	2.6	38	49	-
3700*	19A	-	32DC	5.0 @ 32v	7.5 @ 36.3v	10	133	216	2.6	38	49	-
2800	A55D	175	110AC	-	-	-	222	124	2.5	38	-	-
2000	09	-	12DC	8.4	12.0	15	152	108	1.3	28.6	41, 43, 45, 49	35, 37, 40
2000	10	-	12DC	8.4	12.0	15	152	108	1.3	28.6	41, 43, 45, 49	35, 37, 40
2000	10-6UL	-	12DC	8.4	12.0	15	152	108	1.4	28.6	41, 43, 45, 49	35, 37, 40
2000	11	-	32DC	3.1 @ 32v	5.0 @ 36.3v	6	152	108	1.3	28.6	42, 44, 45, 49	35, 37, 40
2000	12	-	24DC	4.0 @ 24v	6.0 @ 27.2v	7.5	152	108	1.3	28.6	42, 44, 45, 49	35, 37, 40
1800	A53D	100	110AC	-	-	-	196.8	120.6	1.8	28.6	-	-
1500	02	-	12DC	4.8	7.0	9	152	108	1.2	28.6	41, 43, 45, 49	35, 37, 40
1500	02-6	-	12DC	4.8	7.0	9	152	108	1.2	28.6	41, 43, 45, 49	35, 37, 40
1500	03	-	24DC	2.3 @ 24v	3.5 @ 27.2v	4	152	108	1.2	28.6	42, 44, 45, 49	35, 37, 40
1100	27D	-	12DC	3.3	5.0	6	108	60.3	0.28	28.6	41, 43, 45, 49	35, 37, 40
1100	27D-6	-	12DC	3.3	5.0	6	108	60.3	0.31	28.6	41, 43, 45, 49	35, 37, 40
1100	28D	-	24DC	1.3 @ 24v	2.0 @ 27.2v	2.5	108	60.3	0.28	28.6	42, 44, 45, 49	35, 37, 40
1100	27DC	-	12DC	3.3	5.0	6	108	60.3	0.31	28.6	41, 43, 45, 49	35, 37, 40
1000	20A	-	12DC	2.9	4.0	5	102	73	0.40	28.6	41, 43, 45, 49	35, 37, 40
800	20F	-	12DC	2.8	4.0	5	102	73	0.40	19.0	41, 43, 45, 49	35, 37, 40
800	20R	-	12DC	2.8	4.0	5	95.25	60.3	0.28	19.0	41, 43, 45, 49	35, 37, 40
800	21R	-	24DC	1.3 @ 24v	2.0 @ 27.2v	2.5	95.25	60.3	0.28	19.0	42, 44, 45, 49	35, 37, 40
800	20RC	-	12DC	2.8	4.0	5	95.25	60.3	0.28	19.0	41, 43, 45, 49	35, 37, 40
500	26D	-	24DC	0.9 @ 24v	1.3 @ 27.2v	1.5	89	60.3	0.26	19.0	42, 44, 45, 49	35, 37, 40
500	25D	-	12DC	1.9	2.5	2.5	89	60.3	0.26	19.0	41, 43, 45, 49	35, 37, 40
500	25D-6	-	12DC	1.9	2.5	2.5	89	60.3	0.28	19.0	41, 43, 45, 49	35, 37, 40
500	25D-6WC	-	12DC	1.9	2.5	2.5	89	60.3	0.28	19.0	49PWC	-
500	25DC	-	12DC	1.9	2.5	2.5	89	60.3	0.26	19.0	41, 43, 45, 49	35, 37, 40
360	24	-	12DC	2.1	2.5	2.5	89	60.3	0.26	19.0	41, 43, 45, 49	35, 37, 40
360	24-6	-	12DC	2.1	2.5	2.5	89	60.3	0.26	19.0	41, 43, 45, 49	35, 37, 40

\* General Purpose Pump

